

Supporting Drill Information to Alacer Gold Announcement

This document provides supporting drill collar locations and composite assay results for the Ardich drilling program referenced in the announcement “Alacer Gold Announces Additional Positive Drill Results for the Ardich Gold Prospect, including 57.7 Meters at 3.84 Grams per Tonne”, dated November 8, 2018.

Drill collar locations are surveyed in UTM Zone 37N, ED50 grid using differential GPS in units of meters. All drilling was diamond core drilling with HQ and PQ core sizes. HQ is 63.5mm and PQ is 85mm in diameter.

Drill Collar Coordinates

Hole ID	Easting	Northing	Elevation	Azimuth	Dip	End of Hole (m)
AR44	463720.58	4367195.65	1209.65	210	-60	166.70
AR45	463689.80	4367230.79	1206.77	30	-60	145.50
AR46	463997.22	4366481.79	1361.81	30	-65	253.40
AR47	463519.59	4367381.62	1140.42	240	-60	134.40
AR48	463520.10	4367382.54	1140.39	290	-60	92.20
AR49	463503.18	4367281.93	1140.44	230	-60	131.40
AR50	463504.63	4367283.56	1140.23	325	-60	95.00
AR51	463565.86	4367305.19	1165.92	220	-60	119.60
AR52	463565.33	4367306.42	1165.90	315	-60	216.90
AR53	463539.25	4367235.04	1173.45	5	-60	142.90
AR54	463416.02	4367174.77	1187.49	5	-60	110.30
AR55	463417.71	4367177.51	1187.53	70	-60	126.80
AR56	463398.95	4367099.74	1189.41	70	-60	103.60
AR57	463542.67	4367195.01	1172.89	85	-45	148.00
AR58	463397.21	4367098.23	1189.36	155	-60	99.80
AR59	463539.69	4367195.81	1173.04	315	-60	131.70
AR60	463351.87	4367053.34	1206.47	90	-50	57.30
AR61	463147.08	4367388.59	1196.48	45	-60	120.20
AR62	463288.28	4367114.81	1207.12	10	-60	121.40
AR63	463148.46	4367386.11	1196.60	155	-60	124.70

Ardich Drill Intercepts

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments
AR44	-	-	-	-	-	166.70	There is no consecutive 3m mineralization
AR45	-	-	-	-	-	145.50	There is no consecutive 3m mineralization
AR46	107.00	117.00	10.00	0.57	Oxide	253.40	
	131.50	132.50	1.00	5.78	Oxide		
AR47	70.90	82.00	11.10	1.74	Sulfide	134.40	72.90-74.00 Sulfide
	87.20	98.90	11.70	1.62	Oxide		
AR48	36.10	42.10	6.00	1.83	Oxide	92.20	
	46.10	49.10	3.00	1.25	Oxide		
AR49	19.40	26.40	7.00	1.47	Oxide	131.40	
AR50	27.30	39.00	11.70	4.49	Oxide	95.00	37.00-39.00 Sulfide
<i>Including</i>	37.00	38.00	1.00	26.20	Sulfide		
AR51	45.30	48.30	3.00	1.04	Oxide	119.60	
	57.70	65.00	7.30	0.82	Oxide		
	69.00	82.00	13.00	2.37	Oxide		72.00-74.00 Sulfide
<i>Including</i>	71.00	73.00	2.00	8.50	Mixed		72.00-73.00 Sulfide
	86.00	99.40	13.40	0.95	Oxide		
AR52	59.00	70.00	11.00	0.75	Oxide	216.90	
	74.00	79.00	5.00	0.35	Oxide		
	97.40	102.70	5.30	0.62	Oxide		
	121.30	179.00	57.70	3.84	Mixed		55/45 Sulfide-Oxide Zones
<i>Including</i>	121.30	131.50	10.20	5.75	Oxide		122.80-124.80 Sulfide
<i>Including</i>	135.60	147.50	11.90	6.40	Mixed		70/30 Oxide-Sulfide Zones
<i>Including</i>	153.50	158.50	5.00	5.15	Sulfide		
<i>Including</i>	166.10	171.20	5.10	6.42	Mixed		60/40 Sulfide-Oxide Zones
	188.00	204.00	16.00	0.51	Oxide	188.00-188.80 and 190.80-192.80 Sulfide	
AR53	49.60	98.10	48.50	2.69	Oxide	142.90	62.60-63.60 and 67.60-69.60 Sulfide
<i>Including</i>	59.60	65.60	6.00	5.04	Oxide		62.00-63.00 Sulfide
<i>Including</i>	78.60	84.60	6.00	7.06	Oxide		
	106.60	142.00	35.40	0.89	Oxide		70/30 Oxide-Sulfide Zones
AR54	5.00	66.40	61.40	2.22	Oxide	110.30	37.80-38.80 Sulfide
<i>Including</i>	36.80	43.60	6.80	7.14	Oxide		37.8-38.8 Sulfide
<i>Including</i>	49.00	55.40	6.40	7.75	Oxide		
AR55	3.00	27.10	24.10	1.55	Oxide	126.80	
<i>Including</i>	16.00	18.00	2.00	5.49	Oxide		
	31.10	73.60	42.50	2.55	Mixed		32.70-34.50 and 54.60-61.30 Sulfide
<i>Including</i>	44.30	47.80	3.50	6.80	Oxide		

Hole ID	From (m)	To (m)	Interval (m)	Au g/t	Remarks	Depth (m)	Comments	
<i>Including</i>	55.80	59.30	3.50	5.67	Mixed		50/50 Oxide-Sulfide Zones	
<i>Including</i>	63.30	67.30	4.00	7.64	Oxide			
AR56	22.30	48.70	26.40	2.41	Oxide	103.60	32.30-33.30 Sulfide	
<i>Including</i>	34.30	37.30	3.00	6.23	Oxide			
	63.10	79.00	15.90	1.41	Oxide		64.10-65.80 Sulfide	
AR57	-	-	-	-	-	148.00	There is no consecutive 3m mineralization	
AR58	23.90	85.30	61.40	2.04	Mixed	99.80	80/20 Oxide-Sulfide Zones	
<i>Including</i>	50.70	52.70	2.00	6.17	Sulfide			
<i>Including</i>	70.30	76.30	6.00	7.09	Oxide			
AR59	30.50	52.00	21.50	1.55	Oxide	131.70		
	58.50	94.70	36.20	1.67	Oxide			82.00-83.00 and 85.00-88.00 Sulfide
<i>Including</i>	59.50	64.50	5.00	5.34	Oxide			
<i>Including</i>	76.70	79.00	2.30	5.30	Oxide			
AR60	-	-	-	-	-	57.30	Abandoned at 57.30 due to technical problems and re-drill at same location as AR66. Assay results are pending.	
AR61	8.00	108.60	100.60	1.35	Oxide	120.20	Includes isolated intervals of core loss totaling 0.8m. 89.10-90.10 and 102.10-103.30 Sulfide	
<i>Including</i>	82.10	92.10	10.00	3.01	Oxide			
<i>Including</i>	100.10	103.30	3.20	5.01	Oxide			70/30 Oxide
AR62	19.80	84.00	64.20	2.00	Mixed	121.40	85/15 Oxide-Sulfide Zones	
<i>Including</i>	45.30	57.30	12.00	5.21	Oxide			
AR63	44.00	78.30	34.30	1.11	Oxide	124.70		
	85.30	94.60	9.30	0.79	Oxide			

Significant gold intervals reported at a nominal 0.3 g/t gold cut-off and with a maximum 3.5m contiguous dilution are given in Table 1. All thicknesses are down hole length and true widths are not known at this stage.

Material assay results are listed for drill holes having >5.0 meter downhole length averaging >0.3 g/t gold. Holes containing less than 5.0 meters averaging >0.3 g/t have been excluded. The minimum requirement for higher grade subintervals (including) is >3m length with >1 g/t Au.